

ID-Nr. 41429-047 Model IO90.195.120.PS.WDC



Dimensions	
2	1107
Width (external)	1193 mm
Depth (external)	615 mm
Height (external)	1953 mm
Width (internal)	1050 mm
Depth (internal)	522 mm
Height (internal)	1647 mm
Weight / Load	
Weight without interior equipment	424 kg
Distributed load	531 kg/m ²
Maximum load	600 kg
Colouring / Surface finish	
Body colour code	RAL 7016
Body colour	anthracite grey
Body surface finish	textured
Door / Drawer colour code	RAL 5010
Door / Drawer colour	gentian blue
Door / Drawer surface finish	textured
•	
General Information	
Number of doors	2
Door opening angle	89.50°
Depth with open doors	1167 mm
Entry width transport base	1120 mm
Entry height transport base	90 mm
, , , , , , , , , , , , , , , , , , , ,	

94032080

Customs tariff number











safety storage cabinet for lithium-ion batteries ION-PRO-90 Model IO90.195.120.PS.WDC, body colour anthracite grey (RAL 7016), with wing doors in gentian blue (RAL 5010)

Function / construction:

- Robust construction and longevity: robust, high-quality, scratch-resistant outer body with powder-coated textured surface
- **Convenient cabinet entry:** open both doors at the same time with just one hand.
- Integrated potential-free alarm contact for strongly recommended alarm forwarding. Optionally available with relay module and module for remote signalling.
- No unauthorised use: doors lockable with cylinder locking (integration in an existing locking system possible) and locking state indicator (red/green). Permanent locking of the doors by automatic 2-point locking.
- Integrated transport base: In the event of an emergency, immediate evacuation and transport of the cabinet to a safe place outdoors.
- Easy alignment: adjusting aids to compensate for uneven floor
- Smoke detector and temperature sensor for fire detection and forwarding the alarm to the building management system.
- Pressure relief in the head section
- All-around protection: 90 minute fire protection from outside to inside (type 90 / type tested in accordance with EN 14470-1) and for more than 90 minutes fire resistance for fires from inside to outside
- LED display with visual and audible alarm for a quick indication of emergencies without opening the cabinet doors.
- **Fire suppression system:** Triggers in the event of a fire inside the cabinet automatically.







