


## Model GOD.215.135.WDHW











Safe and approved outdoor storage of flammable or toxic gases – for up to 5 x 50-litre gas cylinders

## **Function / construction:**

- robust construction and longevity: completely galvanised and powder-coated structured surface and stainless steel base
- no unauthorised use: lockable turning lever (doors also available with profile cylinder, compatible for locking system)
- easy alignment: adjusting aids to compensate for uneven floor
- easy mounting of connecting pipes and gas fittings: lead-through points in the ceiling of the cabinet
- ventilation: effective ventilation through openings beneath the doors and at the rear wall



Dimensions	
Width (external)	1356.00 mm
Depth (external)	400.00 mm
Height (external)	2149.00 mm
Width (internal)	1345.00 mm
Depth (internal)	370.00 mm
Height (internal)	2070.00 mm
The available internal dimensions can vary depending on the interior equipment package.	

138 kg
390.00 kg/m <sup>2</sup>
600 kg

Ventilation	
Extraction air	75 DN
minimum exhaust air quantity 10 times	10 m³/h
Lead-through possibilities	16

Colouring / Surface finish	
Body colour code	RAL 7035
Body colour	Light grey
Body surface finish	textured
Door / Drawer colour code	RAL 7035
Door / Drawer colour	Light grey
Door / Drawer surface finish	textured

<b>General Information</b>	
x 50-litre gas cylinders	5 piece
Door opening angle	180.00
Depth with open doors	1070 mm
Customs tariff number	94032080

Front view Side view Top view

